

5071 GENERAL PURPOSE INTERIOR LUMINAIRE (SLAVE/MAINS)

APPLICATIONS

The 5070 General Purpose Interior Luminaire (Slave/Mains) is a multi purpose low profile luminaire and is suitable for many internal emergency lighting applications. It is ideal for final exits and emergency escape routes in hotels, restaurants, hospitals, schools and commercial premises as the attractive fitting will blend in with most modern décor.



FEATURES

- Tough Prismatic Diffuser
- Opal Diffuser also available
- Attractive Fitting
- Easy Installation
- Reliable
- UV Stabilised Body Moulding
- Cable Entries Moulded into Body
- Legends Kit available
- 3 Hour Emergency Luminaire
- Designed to Comply to ICEL and British Standards

OPERATION

The 5071 Metal Body Interior Luminaire Fully Recessed (Slave/Mains) is illuminated by an 8 watt fluorescent lamp, powered via a Central Battery System. In the event of a mains failure, emergency illumination is provided for 3 hours. The AC/DC Slaves are available as 24 volt, 50 volt, 110 volt and 230 volt versions, with the latter suitable to work direct from the mains. Note, the mains version can not provide emergency illumination backup in the event of a mains failure. A self-contained version of the luminaire is also available (*Ref 5070*).

A tough Prismatic Diffuser comes as standard, with an Opal Diffuser available as an alternative. The 5071 is manufactured using UV stabilised body moulding, which resists damage to the unit caused by sunlight, allowing the luminaire to maintain integrity over time. A compatible Legends Kit (*Ref 5298/2*) can be supplied to help create inexpensive fire safety signs by fitting a legend panel to the front face of the diffuser.

There is a wide range of ancillary devices and related products which supplements this emergency lighting luminaire range.

APPROVALS : Designed to conform to ICEL 1001: 1999 and BS EN 60598-2-22 1999



SPECIFICATION

	24V	50V	110V	230V
Order Code	5071/8/24	5071/8/50	5071/8/110	5071/8/230
Input Voltage	24 Volt	50 Volt	110 Volt	230 Volt
Power Rating	8.9VA	7.5VA	7.7VA	13VA
Light Source	1 x 8 watt 300mm Coolwhite Fluorescent Tube			
Light Output	275 Lumens			
Emergency Duration	N/A			
Battery Type	N/A			
Charger	N/A			
Recharge Time	N/A			
Dimensions	390 x 186 x 72			
Weight (Kg)	1.3 Kgs			

Optional Extras:-

- 5298/2 Self-Adhesive Deluxe Legend Kit
- Opal Diffuser add suffix /O to the Order Code
- Prismatic Diffuser add suffix /P to the Order Code